

SPECIFICATIONS

FREQUENCY RESPONSE	32Hz - 125Hz
MAXIMUM ACOUSTIC OUTPUT	110dB
AMPLIFIER TYPE	Class D with Analog Preamp Stage
AMPLIFIER POWER	50 W RMS / 200 W Peak
WOOFER	10" Long-Throw IMG
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Front- Firing Tube Port
INPUTS	Dual RCA/LFE Line In, WA-2 Wireless Port
HEIGHT	400mm / 15.76"
WIDTH	318mm / 12.5"
DEPTH	408mm / 16.1"
WEIGHT	14.06 kg / 31 lbs
FINISH	Black Ash, Dark Apple, Matte White

C 910 SUB

SUBWOOFFR

50 YEAR LEGACY

For more than half a century, Jamo has designed and engineered high-performance audio products to integrate beautifully into any environment. The Jamo Concert 9 subwoofers blend premium low frequency performance with a modern, luxurious design and high quality finishes, creating exceptional acoustics surpassed only by their beauty. These subwoofers are the ideal complement for the Jamo Concert 9 Series II speakers, or any high-performance audio system in the spaces where you live and play.

EXCEPTIONAL RUMBLE

The Concert 9 subwoofers feature a rigid injection molded graphite (IMG) woofer cone creating a pure, fast motion with less cone break-up for clean, tight bass – while being exceptionally light, allowing the subwoofers to achieve some of the highest output in their class. The tube port's flared design minimizes port noise and delivers exceptional low frequency extension. A front-firing port allows for versatility in placement tight against a wall or in a cabinet.

THE POWER TO PERFORM

Room-shaking bass requires an amplifier capable of providing accurate and ideal power requirements when needed. The Class D audiophile grade amplifiers in the JAMO C 910 and C 912 subwoofers provide impressive low end with head room to spare. Dual RCA inputs allow for connection to AVRs, processors, and integrated amplifiers, while WA-2 wireless kit compatibility provides for easy, wire-free installation. A continuously variable crossover filter and phase switch allows for fine-tuning of the subwoofer for optimal performance in any specific room.

WIRELESS READY

The JAMO C 910/912 SUB incorporate a built-in wireless input receiver, allowing the audio signal to be transmitted from the source and received from the WA-2 transmitter (sold separately) so the subwoofer can be placed anywhere in the room. Not only does this make for a clean, cable-free installation, it also allows the subwoofer to be positioned for the most optimal performance. Using 2.4Ghz wireless technology, the WA-2 system ensures true audiophile, high resolution audio with exceptionally low latency – providing the freedom of wireless without compromising quality.

