

The Studio7 is our new range of loudspeakers developed to revitalise the Jamo brand, whilst bringing a new level of quality to the consumer. The result is a range that not only sounds excellent but is also visually striking and undeniably Scandinavian. The range owes its name to the 7° tilt that helps the products look so distinctive. Our engineers have used top tier components, expertly voiced and validated with countless hours of listening to bring you a rare combination of both aesthetics and audio performance unrivalled in its class. Welcome to the Studio7.



PURE SCANDINAVIAN SOUND
SINCE 1968



S7-25HCS HOME CINEMA SYSTEM

Thanks to our 5.0 home cinema systems all in one box, you can hear the slightest detail, be surprised by a sound suddenly springing up behind you and be completely immersed in your movies. Your films, series, TV-shows take on a whole new dimension.

The home cinema system also contributes greatly to improving the comfort of your television set in everyday life. Dialogues are more intelligible and soundtracks more detailed.

The Studio S7-25HCS consists of :

- 2 x S7-25F floorstanding speakers
- 2 x S7-15B bookshelf speakers
- 1 x S7-25C center channel

EUROPEAN DESIGN - SCANDINAVIAN ROOTS

With its minimalist aesthetic, clean lines and meticulous attention to detail, the Studio7 series is a great example of form following function and ushers in a new era of performance for Jamo. Brimming with technical innovation our design team have created a speaker that is timeless and would grace any home. Inspired by nature the Studio7 series is a tribute to our two founders, Preben Jacobsen and Julius Mortensen.



The high frequency duties are carried out by the all new 1-inch tweeter unit featuring a copper faraday ring which increases sensitivity and reduces non-linear distortion. The tweeter and surround is made from fabric and exhibits excellent distortion characteristics and wide bandwidth, for a non-fatiguing yet detailed sound.

The High Frequency waveguide was optimised using Jamo's exclusive COMSOL software model. Validation of the waveguide and tweeter performance was achieved through countless hours of real-world testing to ensure consistency, reliability and performance even at high sound pressure levels for extended periods.

NATURAL BASS

The bass drivers feature embossed paper cones, high strength motor assemblies incorporating aluminium inductance shorting rings that both enhance power handling and lower distortion. The aluminium shorting ring lowers distortion for clean, dynamic bass and increases power handling as the aluminium ring acts as a heat sink.

The embossed paper cone with « Thor's Hammer » detailing increases the rigidity to improve the transient response for that snappy yet natural bass.

7° TILTED CABINET – A DISTINCTIVE DESIGN FOR A NEW SOUND EXPERIENCE

7 really is the magic number for the new Studio 7. To ensure a coherent sound stage, we have time aligned the acoustic centres of the drive units by tilting the cabinet back and mounting it on a plinth that houses the speaker crossover. This helps minimise any timing anomalies that can occur in a more traditional enclosure.











S7-25HCS HOME CINEMA SYSTEM

REDUCING DIFFRACTION

When a speaker driver produces sound, some energy is spread across the baffle of the speaker towards the edge of the cabinet. If that energy hits a hard cabinet edge, a smaller version of this energy is reflected back towards the driver causing a time shifted, low level signal that can corrupt the sound of the driver leading to distortion. By rounding the cabinet edge, this energy gently dissipates more naturally, and does not colour the signal being produced by the driver.



QUIET CABINET FOR INCREASED RESOLUTION

The Jamo Studio speakers' cabinet walls are thicker (15 mm MDF with 18 mm Front baffle) and critically braced to ensure a low degree of « self-noise ». This allows you to hear more low-level detail and increases resolution when playing at any output level compared to competing products in their class. In short, you get to hear more of what you want and less of what you don't.



HIGH QUALITY CROSSOVER

The crossover is housed in its own sealed plinth to minimise the possibility of any interaction between the large bass driver magnet and the inductors in the crossover. Special attention was paid to the topology and component selection. Mylar and non-polarised electrolytic capacitors are used along with both iron and air core inductors and 25 W resistors to perfectly blend the speaker drivers achieving the highest level of transparency throughout the audio band.



2 COLOURS - INSPIRED BY NORDICS NATURE

Our colours have been chosen from the chromatic palette of Scandinavian landscapes: the dark blue is inspired by the Norwegian fjords and the grey cloud from the fog hanging over a Finnish forest. Our signature blue fjord brings an emotional touch to your interior whilst Grey cloud integrates seamlessly into the modern home.

The Jamo Studio7 will enhance your living space no matter which colour you choose.



STUDIO7 IS ALL ABOUT HYGGE

Hygge - « To create a warm atmosphere and enjoy the good things in life with family and friends. » So, seat comfortably, relax and enjoy a sound as pure as Scandinavian air.



STUDIO7 SERIES















	S7-27F	\$7-25F	S7-17B	S7-15B
	Floorstanding speakers (pair)	Floorstanding speakers (pair)	Bookshelf speakers (pair)	Bookshelf speakers Surround speakers (pair)
Enclosure Type	2-Way bass reflex	2-Way bass reflex	2-Way bass reflex	2-Way bass reflex
HF Drivers	1''/2.54 cm Vented tweeter with a fabric dome	1''/2.54 cm Vented tweeter with a fabric dome	1''/2.54 cm Vented tweeter with a fabric dome	1''/2.54 cm Vented tweeter with a fabric dome
LF Drivers	Dual 6.69" / 17 cm woo- fers - Embossed paper cone with thor's hammer	Dual 5.5" / 14 cm woo- fers - Embossed paper cone with thor's hammer	Single 6.69" / 17 cm woofer - Embossed paper cone with thor's hammer	Single 5.5" / 14 cm woofer - Embossed paper cone with thor's hammer
Sensitivity*	90 dB @ 2.83 V/1 m	90 dB @ 2.83 V/1 m	87.2 dB @ 2.83 V/1 m	86.3 dB @ 2.83 V/1 m
Frequency response (±3 dB)	67 Hz - 21 kHz	69 Hz - 21 kHz	64 Hz - 25 kHz	71 Hz - 22 kHz
Max Low-end extension (room dependent)	32 Hz	35 Hz	40 Hz	44 Hz
Maximum output (peak sound pressure level at 1m)	107.8 dB	107 dB	104.2 dB	102.6 dB
Nominal Impedance	4 ohms	4 ohms	4 ohms	4 ohms
Continuous Power handling	120 W	100 W	100 W	85 W
Recommended Amp. Power	40-250 W	40-200 W	40-150 W	25-120 W
Dimensions (unit) (H x W x D)	85.5 x 23 x 38 cm 33.6 x 9 x 15 inches	80.5 x 20 x 34 cm 31.7 x 7.9 x 13.4 inches	36.5 x 23 x 38 cm 14.4 x 9 x 15 inches	32 x 20 x 34 cm 12.6 x 7.9 x 13.4 inches
Product Weight (unit)	17.93 kg / 39.5 lbs	12.32 kg / 27.2 lbs	8.37 kg / 18.5 lbs	5.93 kg / 11 lbs
Available Finish	Blue Fjord vinyl Grey Cloud vinyl	Blue Fjord vinyl Grey Cloud vinyl	Blue Fjord vinyl Grey Cloud vinyl	Blue Fjord vinyl Grey Cloud vinyl
Included accessories	Metal spikes (8) Rubber feet (8)	Metal spikes (8) Rubber feet (8)	Rubber feet (8)	Rubber feet (8)
Optional	-	-	-	Wall mounting brackets

^{*}SPL at 1m, half-space anechoic with 2.83 V input



STUDIO7 SERIES





	\$7-25C	\$7-43C	
	Center channel	Center channel	
Enclosure Type	2-way bass reflex	2-way bass reflex	
HF Drivers	1′′/2.54 cm Vented tweeter with a fabric dome	1''/2.54 cm Vented tweeter with a fabric dome	
LF Drivers	Dual 5.5'' / 14 cm woofers Embossed paper cone with Thor's Hammer	Quad 3.3'' / 8.4 cm woofers Embossed paper cone with Thor's Hammer	
Sensitivity*	90.2 dB @ 2.83 V/1 m	91.2 dB @ 2.83 V/1 m	
Frequency response (±3 dB)	82 Hz - 21 kHz	123 Hz - 21 kHz	
Max Low-end extension (room dependent)	51 Hz	73 Hz	
Maximum output (peak sound pressure level at 1 m)	107.2 dB	108.2 dB	
Nominal Impedance	4 ohms	4 ohms	
Continuous Power handling	100 W	100 W	
Recommended Amp. Power	25-200 W	25-150 W	
Dimensions (unit) (H x W x D)	18 x 54 x 23 cm 7 x 21.3 x 9 inches	12.5 x 60 x 17.1 cm 4.9 x 23.6 x 6.3 inches	
Product Weight (unit)	7.85 kg / 17.3 lbs	6.32 kg / 13.9 lbs	
Available Finish	Blue Fjord vinyl Grey Cloud vinyl	Blue Fjord vinyl Grey Cloud vinyl	

*SPL at 1m, half-space anechoic with 2.83 V input



PURE SCANDINAVIAN SOUND SINCE 1968